



COMBINED SEWER CLEANING

Flexibility to handle a wide range of applications

Elegance 2.0

Top performance, outstanding reliability and excellent design

The Elegance 2.0 impresses with modern looks as well as robust and dependable technology. Decades of experience and cutting-edge development work are perfectly matched in this product line. It uses materials which unite low weight and high resistance.

Triplex plunger pumps are available for the high-pressure system, and KAISER vane pumps or positive displacement blowers for the vacuum system. The respective pumps are located between the driver's cab and the tank. The components are hydraulically or mechanically driven depending on power requirements. This is performed by means of the power take-off on the carrier vehicle or a separate intermediate gearbox.

Versatility and high operator comfort

The well-conceived modular system allows the configuration of a broad spectrum of vehicles, from the compact 2-axle vacuum vehicle to the top-of-the-range 4-axle combination vehicle. The option of side-mounted water tanks in polyethylene or stainless steel enables the tank layout to be optimally adapted to the needs of the individual customer.


Vehicle operation has been designed with a focus on simple handling. A wide range of additional options as well as different suction boom versions, various jetting hose reels or ADR / ATEX round off the Elegance series.



DESIGN AND FUNCTIONALITY

INTELLIGENT DESIGN ISN'T JUST VISIBLE – IT'S ALSO PALPABLE. SUPERSTRUCTURE AND CARRIER VEHICLE FORM A PERFECTLY COORDINATED WHOLE.









TECHNICAL SPECIFICATIONS AND EQUIPMENT

Tank capacity	2-Axle Truck (18 to)	3-Axle Truck (26 to)	4-Axle Truck (32 to)
Sludge tank capacity (I)	5500-7300	10000-11400	12750-15000
Water tank capacity (I)	2700-5300	3000-5600	3200-5500
Wheelbase (mm)	3690-4300	3100-4500	4300-5300

Operation and control

- > Control panel towards the rear of the vehicle
- > Radio remote control with all the relevant operating functions
- > Memory function for performance parameters (option)

High-pressure water system

- High-pressure pumps with flow rates of 68 l/min and 50 bar up to 410 l/min and 170 bar
- Jetting hose reel at side with manual or hydraulic drive for HP hoses of ½" to ¾", with manual or forced winding
- Jetting hose reel at rear with hydraulic drive for HP hoses of 3/4" to 11/4"; with hydraulically slewable or fixed mounting including forced winding
- > Jetting hose reel model KSA for the combination of HP jetting hose and suction hose
- > Winter protection for temperatures of -5° to -20° C

Vacuum system

- Rotary vane vacuum pumps with water cooling and air flow rates of 984 m³/h to 1700 m³/h
- Rotary piston vacuum pumps with air flow rates of 1550 m³/h to 3900 m³/h
- Rear suction hose reel hinged, suction hose reel on tank in simple construction or with hose boom, for suction hoses with a diameter of 80, 100, 120 or 150 mm
- Various hydraulic suction boom types in 4", 5", 6", as basic or extended version

Tank structure

- > Tank in carbon steel or stainless steel
- > Tank structure with individual tank layout
- > Tipping system for complete emptying of the tank

SUPERSTRUCTURE DESIGN AND OPTIONS

Modular superstructure design

The Elegance line offers different versions for the ideal combination of fresh water and sludge tank, while simultaneously ensuring optimal axle load distribution and maximum payload.



Fresh water in front section of the tank, with permanent separation from sludge tank



Fresh water in side-mounted water tanks in polyethylene or stainless steel



Combination of fresh water tanks at front and sides

High-pressure and vacuum pumps



Rotary piston or rotary plunger vacuum pumps



Triplex high-pressure pumps





Combined suction/jetting boom

Standard suction boom



Spiral suction boom

Suction hose reel



Telescopic suction boom

Telescopic suction boom 360°



Jetting hose reel

Slewable reel



Fixed reel





Winter protection



Metre counter



KAISER MORO ELEGANCE, THE FIRST SEWER CLEANING VEHICLE WITH A CLEAR DESIGN LANGUAGE





FOR YOUR APPLICATION THE SUITABLE KAISER PRODUCT

Water treatment by

means of flocculation.

RECYCLING VEHICLES

Top performance and

reliability under the most

difficult sewer conditions.

WATER TREATMENT VEHICLES

COMBINATION VEHICLES

JETTING AND VACUUM VEHICLES

Designed to meet the

highest performance

requirements in the

respective field.

DRY VACUUM VEHICLES

High-performance

wet materials.

vacuuming of dry and

HYDROVACS

High productivity with

a rugged and reliable

technology.

MOBILE-WALKING EXCAVATOR

Impressive technology

to master tough

challenges.

ROAD-RAIL EXCAVATOR



Perfectly matched to the application of the railway environment.

AquaStar	AquaStar WT	Elegance 2.0	Tornado	Cerberus	CV-Series	S12 Allroad	S22RR
Eco 3.0	KolDry	AquaStar	Elegance 2.0	Hercules	Urban X	S12 4x4	
EcoCycler		Combi Eur-Mark	Twister			S10	
CityCycler		Tornado	Special vehicles			S 2	
EcoCombi		BasicLine					

CityCleaner



info@octopuse.co.za www.octopuse.co.za KAISER AG Vorarlbergerstrasse 220 9486 Schaanwald, Liechtenstein T +423 377 21 21 kaiserag@kaiser.li www.kaiser.li

Flexibility to handle

a wide range of

applications.

MORO KAISER S.R.L. Via Pontebbana, 16 33080 Fiume Veneto (PN), Italy T +39 0434 951 211 infomoro@morokaiser.it www.morokaiser.it

KAISER PREMIER LLC 2550 E. Bijou Ave. Fort Morgan, CO 80701, USA T +1 970 542 1975 sales@kaiserpremier.com www.kaiserpremier.com

OY EUR-MARK AB Jakobstadsvägen 39 66900 Nykarleby, Finland T +358 20 73 45 800 info@eurmark.fi www.eurmark.fi

KAISER Fahrzeugtechnik GmbH Gewerbestraße 4 6710 Nenzing, Austria T +43 5525 641 80 mail@kaiser-fahrzeugtechnik.at

www.kaiser-fahrzeugtechnik.at

KAISER Eastern Europe s.r.o. Priemvselná 604/5 922 02 Krakovany, Slovakia T +421 33 7353 500 kaiser@kaiser-ee.sk www.kaiser-ee.sk