



X-60 Datasheet

The Scanprobe **X60** pipeline inspection system redefines industry standards with its capability to inspect pipelines up to 300mm. It introduces groundbreaking features like PDF editing, clock position observations, extended battery life, and disc brakes for enhanced control and safety. Seamless integration with popular platforms like Outlook and WhatsApp streamlines report sharing, while selecting **mina** plus or **WinCan ProTouch** (Optional) ensures detailed and efficient reporting. With screen size options of 8 or 10 inches, the X-60 offers versatility to suit diverse user preferences. In essence, it represents the pinnacle of pipeline inspection technology, delivering comprehensive and reliable results with ease.



Rod Length	60 metres / 197 foot
Rod Diameter	12.0mm
System Weight	8" - 25.4 kg / 10" - 26.3 kg
Coiler Dimensions	W 441mm, H 837mm, L 656mm
Camera Diameter	44mm
Pipe Use	50mm to 300mm Ø, 2" to 12" Ø
Sonde Locator	33kHz or 512Hz (optional)
Distance Counter	Meters/Feet
Self-levelling camera	Yes / Dual bearing stability
Camera Resolution	PAL: 720Hx576V
Light Source	High Power LEDs - White 5700K
Operating Temperature	-10°C - +50°C
Output	USB-C
Battery type	Li-ion
Battery Life	Up to 12 hours
Capacity	13.04Ah
Charge Current	1.5A
Nominal Voltage	7.4V
Charging Options	12V & 240V
IP Rating	Camera: IP68, Coiler: IP54
Approvals	CE and UKCA



Connectivity

